



ElectriBank 12V 70Ah ESS Deep-Cycle Battery

ELECTRICAL SPECIFICATIONS

Nominal Voltage	12.8 V
Fully Charged Voltage	13.2 - 13.4V
Nominal Capacity	70 Ah (130Ah PbEq)
Capacity @ 25A	160 min
Energy	902 Wh
Efficiency	99%
Resistance	30 mΩ
Self Discharge	<2% per month
Maximum in Series/Parallel (Rec)	4 modules

DISCHARGE SPECIFICATIONS

Maximum Continuous Discharge Current	100 A
Peak Discharge Current	250 A
BMS Discharge Current Cut-Off	300 A (±50 A)
Recommended Low Voltage Disconnect	11 V
BMS Discharge Voltage Cut-Off	8.8 V
Reconnect Voltage	10.8 V
Short Circuit Protection	200-600 μs

TEMPERATURE SPECIFICATIONS

Discharge Temperature	-20 to 65 degC
Charge Temperature	0 to 60 degC
Storage Temperature	-10 to 45 degC
BMS High Temperature Cut-Off	80 degC

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	260 x 130 x 210 mm
Weight	7.5 kg
Terminal Type	M8 (supplied)
Terminal Torque	9 -11 Nm
Case Material	ABS
Enclosure Environmental Protection	IP56
Cell Type – Chemistry	Prismatic – LiFePO ₄
LCD Display Type	Volts, Capacity, Temp

CHARGE SPECIFICATIONS

Recommended Charge Current	10 - 50 A
Maximum Charge Current	100 A
BMS Charge Current Cut-Off	200 A (±50 A)
Recommended Charge Voltage	14.2 - 14.6 V
BMS Charge Voltage Cut-Off	15.6V
Reconnect Voltage	15.2 V
Balancing Voltage	14.4V



PERFORMANCE CHARACTERISTICS

The ElectriBank 70AH ESS is a high performance lithium LiFePO₄ deep-cycle Energy Storage System (ESS) battery that is lightweight, durable and long-life with water resistance to IP56 standards.

The ElectriBank 70Ah ESS battery can be charged using most 12-16V charging systems including AC-DC/-DC converters and chargers, solar panels, fuel generators, alternators and wind generators etc. The ElectriBank range of ESS batteries were designed for tough Australian conditions and can withstand the rigours of touring, boating, camping and 4WD applications.

The ElectriBank range has the added advantage of delivering high burst current output, well above industry standards to provide exceptional power output capability.

ElectriBank ESS batteries are dry-cell and require no maintenance other than charging and can maintain charge when stored for up to 12 months with minimal loss.

ElectriBank ESS batteries are safe, reliable and made with 100% organic anode and cathode materials so both safe for you and the environment.

Welcome to the new age of Lithium, welcome to ElectriBank.